

- **Cleaning of hollow fibre membrane of membrane assembly - in which cleaning liquid flows through tube under membrane component to clean U-shaped membrane reversely, and compressed air is passed through another tube to clean the outside of membrane.**

L20 ANSWER 87 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD

AN 1999-528184 [45] WPINDEX

DNC C1999-155468

DC J01

IN LU, X

PA (MOTI-N) MOTIANMO TECH ENG CO TIANJIN TEXTILE ENG

CYC 1

PI CN 1221648 A 19990707 (199945)* 1p

ADT CN 1221648 A CN 1998-125099 19981208

PRAI CN 1998-125099 19981208

AN 1999-528184 [45] WPINDEX

AB CN 1221648 A UPAB: 19991103

Cleaning of a hollow fibre membrane with external compressed air features that the membrane assembly has a U-shaped membrane that is reversed fixed under the **membrane** assembly. During **cleaning**, the cleaning liquid flows through a tube under **membrane** component to **clean** the U-shaped **membrane** reversely. Compressed air is passed through another tube to **clean** the outside of **membrane**. The **mixture of cleaning liquid** and compressed **air** after cleaning is discharged through the third tube.

ADVANTAGE - Simple structure, high cleaning efficiency and easy operation.
Dwg.0